World Class Printing Systems
for **Real World Applications**

CO*Pilot 128*

SQUID INK DELIVERS WHAT YOU NEED

The CoPilot 128 ink jet printing system offers the durability, versatility and productivity that you have come to rely on from Squid Ink. Whether you are printing lot codes on coated cartons, bar codes on corrugate cases, or product information and logos on PVC pipe you're sure to find the right solution with Squid Ink's new CoPilot 128.

INDUSTRIAL DESIGN, USER FLEXIBILITY

The system is capable of running oil-based or solvent-based inks to print up to 185 dpi at 135ft/min on a variety of substrates. For non-porous applications, users have the option of utilizing Squid Ink's solvent-based inks to print a number of pigmented inks on a variety of non-porous products like, coated cartons, plastics, glass, shrink wrap, metals, and more. Squid Ink's PZ-1000 ink for porous substrates offers low-maintenance performance, eliminating the need for auto-priming functions and offering better ink utilization than competitive systems.

PRINTING MADE EASY

CoPilot 128's 4.3" full color touchscreen provides access to the system's internal messages and print functions. Messages are created and edited on Squid Ink's easy-to-use Orion™ PC Software and transferred via Ethernet or USB device. For larger applications, a virtually unlimited number of CoPilot 128 printing systems can be connected via Ethernet and controlled through one central Orion™ print station.

MAXIMIZE YOUR UPTIME

The CoPilot 128 is designed to meet the harsh demands of your application. The printer features a durable touchscreen, industrial strength printhead construction, and print engines designed for industrial applications, not office applications. You can be confident that CoPilot 128's rugged design will withstand the most abusive industrial environments while providing superior quality print. The CoPilot also features a large 500ml cartridge or bag ink system. The generous ink volume allows users to keep their line running, reducing downtime and maximizing ROI.

INK JET CODING AT THE RIGHT PRICE

As one of the newest addition to Squid Ink's growing family of marking and coding systems, the CoPilot 128 gives users more choices for their coding applications. Any way you look at it, Squid Ink's CoPilot 128 provides users with an affordable solution to meet their ink jet coding needs.

THE RIGHT SOLUTION

Rugged design. Low maintenance operation. User friendly software. Low cost of ownership. Your benefits go on an on. When it comes to industrial ink jet printing, rely on Squid Ink to provide the right solution for your coding and marking needs.

SQUID INK

1) The CoPilot 128 utilizes oil-based or solvent-based inks for printing on a wide range of porous or non-porous substrates.

2) The system has the flexibility to be configured to print horizontally, at an angle, or in down shooter position.

3) A 4.3" full color touchscreen provides access to the systems internal messages and print functions.

4) The bag ink agitator system is an ideal solution for users printing with pigmented inks.

SYSTEM SPECIFICATIONS:

- **Print Technology -** Piezo impulse printhead technology
- **Maximum Print Height -** .7" (1.8 cm) per printhead
- **Vertical Print Resolution** 185 dpi capable of printing razor-sharp graphics, small character text, and scannable bar codes
- **Horizontal Print Resolution -** 205 dpi
- **Print Speed -** Up to 135 feet/min. (41 m/min.) @ 205 dpi
- **Time & Date -** Internal real time clock with battery back-up
- **Product Sensor -** External diffuse beam photocell standard
- **Communication Interface -** One USB host and one Ethernet input
- **Touchscreen -** 4.3" (10.9 cm) full color touchscreen display
- **Ink Cartridge Volume -** 500ml cartridge or bag
- **Low Ink Indicator -** Message alert on touchscreen, LED light beacon optional
- **Substrate Capabilities -** Porous or Non-Porous surfaces
- **Electrical Requirements -** 100 - 240 VAC, 50/60 Hz
- **Operating Environment -** 34°F - 104°F (1° - 40°C)
- **Agency Certifications -** CE, TUV pending

OPTIONAL ACCESSORIES

- **Encoder -** For operation with variable speed conveyors
- **Bar Code -** Laser Scanner allows scan and print message retrieval
- **External Light Beacon -** Indicates low ink levels
- **Conveyor Mounting Bracket -** Provides stable mount to conveyor or other material handling equipment
- **Floorstand -** Includes mounting brackets and legs with leveling feet; 59" (1.5m) total heights
- **Pigmented Ink Agitation System -** Allows for printing of pigmented inks
- **Starter Kit -** Includes ink, cleaner and flush solution, printhead wipes, hand cleaner and latex gloves

SOFTWARE SPECIFICATIONS

- **Time & Date -** Full time and date functionality including expiration date and Julian Dates.
- **Item Numbering -** Sixteen counters, one of which can be a daily counter.
- **Shift Codes -** Four programmable shift codes with automatic rollover
- **Bar Codes -** All standard bar codes including 2D
- **Fonts -** Arial, Arial Bold, Courier, Tahoma Bold and Lucida resident fonts for use in variable data elements. Static elements in any Windows® font
- **Logos -** Most image files supported with Orion Graphical Interface Software
- **Printing Features -** Reverse, invert, rotate, repeat. Print on/off button
- **Message Length -** Up to 120"
- **Number of Messages -** 1GB storage space will store approximately 1000+ messages
- **Ink Usage -** Shown in Orion™ PC Software
- **User Data Prompts -** Prompts for user input at start of print job by manual input on touchscreen

SQUID INK®

SQUID INK CODING & MARKING SOLUTIONS

EASTEY CASE SEALING & SHRINK PACKAGING EQUIPMENT

AFM SHRINK SLEEVE & LABELING SOLUTIONS

COGENT TECHNOLOGIES INFRARED INK DRYING FOR MAILING & PACKAGING

ENGAGE *technologies corporation*