

EC-JET1000



EC-JET

Continuous ink jet printers

This affordable, compact, and efficient CIJ printer includes features that are typically only available on more expensive products.

The EC-JET1000 includes an operator-friendly colour touch screen display for easy code creation and selection of printing functions.

Quality materials and components ensure reliable operation over a longer useful life than other entry level CIJ printers.

High Value Features

- Durable stainless-steel cabinet
- Sealed printhead for reduced maintenance
- Easy-to-use colour touch screen display
- Durable ruby nozzle for long life reliability
- RFID to prevent accidental use of incorrect ink or solvent
- Reverse printing function

Special Functions

- Easily adjustable print height, width, and position
- Graphics and message input via USB flash drive
- Backup, restore, and software update by USB flash drive
- Simple character/message bolding function
- Optional remote communication interface
- Customizable shift codes




Other Features

- Unique three-door design for easy maintenance access
- Compact cabinet for fitting in tight spaces and easy relocation
- Efficient design for reduced fluid consumption
- Advanced Viscosity Control System to ensure print clarity and stability



Technical Specifications

SPECIFICATION	Description
Printing system	Continuous Ink Jet
Ink Types	Dye
Solvent Type	MEK
Cabinet Material	Industrial Grade Stainless-steel
Display Type	Colour LCD Touch Screen
Display Size	5.6"
Nozzle Size	60µm
Character Height	Up to 24 Dots
Maximum Print Speed	2 m/sec (line speed)
Character Print Speed	1482 Characters per second
Print Lines	1-3 Lines - dependent on character dot matrix
Characters per Message	Maximum 2048
Number of Stored Messages	Maximum 90
External Inputs	USB memory
Alarm Light Output	Yes
Data Input	Touch Screen, RS-232C communication (optional)
Printhead Cable Length	2.5m
Cabinet Size	290mm Deep x 325mm Wide x 558mm High
Printhead Size	42mm dia x 170 mm length
Power	AC 110-125 60hz
Electrical Approval Provided	ESA
Weight	18.3kg
Weight	25 kg



„USB interface”



„Touch-screen operating system”



For more information, contact
Tigerpak Industrial Supplies,
6810 Kitimat Rd, Unit 1,
Mississauga, Ontario, L5N 5M2, Canada.

Telephone:
Ontario (289) 328-0651, (877) 538-8078
Quebec (514) 587-2607, (855) 296-4372

E-mail: Sales@Tigerpak.ca Info@Tigerpak.ca
Website: www.tigerpak.ca

